

MLFB-Ordering data

6SL3224-0BE22-2AA0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																																								
Input <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Line voltage</td><td>380 ... 480 V ± 10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> <tr> <td>Rated current with line reactor</td><td>6.10 A</td></tr> <tr> <td>Rated current without line reactor</td><td>7.60 A</td></tr> </table>	Number of phases	3 AC	Line voltage	380 ... 480 V ± 10 %	Line frequency	47 ... 63 Hz	Rated current with line reactor	6.10 A	Rated current without line reactor	7.60 A	<table> <tr> <td>Power factor λ</td><td>0.85</td></tr> <tr> <td>Offset factor $\cos \varphi$</td><td>0.95</td></tr> <tr> <td>Efficiency η</td><td>0.97</td></tr> <tr> <td>Sound pressure level (1m)</td><td>50 dB</td></tr> <tr> <td>Power loss</td><td>0.14 kW</td></tr> </table>	Power factor λ	0.85	Offset factor $\cos \varphi$	0.95	Efficiency η	0.97	Sound pressure level (1m)	50 dB	Power loss	0.14 kW																				
Number of phases	3 AC																																								
Line voltage	380 ... 480 V ± 10 %																																								
Line frequency	47 ... 63 Hz																																								
Rated current with line reactor	6.10 A																																								
Rated current without line reactor	7.60 A																																								
Power factor λ	0.85																																								
Offset factor $\cos \varphi$	0.95																																								
Efficiency η	0.97																																								
Sound pressure level (1m)	50 dB																																								
Power loss	0.14 kW																																								
Output <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>400 V</td></tr> <tr> <td>Rated current (LO)</td><td>5.90 A</td></tr> <tr> <td>Rated current (HO)</td><td>5.90 A</td></tr> <tr> <td>Max. output current</td><td>11.80 A</td></tr> <tr> <td>Rated power IEC 400V (LO)</td><td>2.20 kW</td></tr> <tr> <td>Rated power NEC 480V (LO)</td><td>3.00 hp</td></tr> <tr> <td>Rated power IEC 400V (HO)</td><td>2.20 kW</td></tr> <tr> <td>Rated power NEC 480V (HO)</td><td>3.00 hp</td></tr> <tr> <td>Pulse frequency</td><td>4 kHz</td></tr> <tr> <td>Output frequency for vector control</td><td>0 ... 200 Hz</td></tr> <tr> <td>Output frequency for V/f control</td><td>0 ... 550 Hz</td></tr> </table>	Number of phases	3 AC	Rated voltage	400 V	Rated current (LO)	5.90 A	Rated current (HO)	5.90 A	Max. output current	11.80 A	Rated power IEC 400V (LO)	2.20 kW	Rated power NEC 480V (LO)	3.00 hp	Rated power IEC 400V (HO)	2.20 kW	Rated power NEC 480V (HO)	3.00 hp	Pulse frequency	4 kHz	Output frequency for vector control	0 ... 200 Hz	Output frequency for V/f control	0 ... 550 Hz	Ambient conditions <table> <tr> <td>Cooling</td><td>Internal air cooling</td></tr> <tr> <td>Cooling air requirement</td><td>0.024 m³/s (0.848 ft³/s)</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3280.84 ft)</td></tr> </table> Ambient temperature <table> <tr> <td>Operation LO</td><td>0 ... 40 °C (32 ... 104 °F)</td></tr> <tr> <td>Operation HO</td><td>0 ... 50 °C (32 ... 122 °F)</td></tr> <tr> <td>Transport</td><td>-25 ... 55 °C (-13 ... 131 °F)</td></tr> <tr> <td>Storage</td><td>-25 ... 55 °C (-13 ... 131 °F)</td></tr> </table> Relative humidity <table> <tr> <td>Max. operation</td><td>95 % RH, condensation not permitted</td></tr> </table>	Cooling	Internal air cooling	Cooling air requirement	0.024 m ³ /s (0.848 ft ³ /s)	Installation altitude	1000 m (3280.84 ft)	Operation LO	0 ... 40 °C (32 ... 104 °F)	Operation HO	0 ... 50 °C (32 ... 122 °F)	Transport	-25 ... 55 °C (-13 ... 131 °F)	Storage	-25 ... 55 °C (-13 ... 131 °F)	Max. operation	95 % RH, condensation not permitted
Number of phases	3 AC																																								
Rated voltage	400 V																																								
Rated current (LO)	5.90 A																																								
Rated current (HO)	5.90 A																																								
Max. output current	11.80 A																																								
Rated power IEC 400V (LO)	2.20 kW																																								
Rated power NEC 480V (LO)	3.00 hp																																								
Rated power IEC 400V (HO)	2.20 kW																																								
Rated power NEC 480V (HO)	3.00 hp																																								
Pulse frequency	4 kHz																																								
Output frequency for vector control	0 ... 200 Hz																																								
Output frequency for V/f control	0 ... 550 Hz																																								
Cooling	Internal air cooling																																								
Cooling air requirement	0.024 m ³ /s (0.848 ft ³ /s)																																								
Installation altitude	1000 m (3280.84 ft)																																								
Operation LO	0 ... 40 °C (32 ... 104 °F)																																								
Operation HO	0 ... 50 °C (32 ... 122 °F)																																								
Transport	-25 ... 55 °C (-13 ... 131 °F)																																								
Storage	-25 ... 55 °C (-13 ... 131 °F)																																								
Max. operation	95 % RH, condensation not permitted																																								

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM240

MLFB-Ordering data

6SL3224-0BE22-2AA0



Figure similar

Mechanical data		Connections	
Degree of protection	IP20 / UL open type	Line side	
Size	FSB	Version	screw-type terminal
Net weight	4.00 kg (8.82 lb)	Conductor cross-section	1.00 ... 6.00 mm² (AWG 18 ... AWG 10)
Width	153 mm (6.02 in)	Motor end	
Height	270 mm (10.63 in)	Version	Screw-type terminals
Depth	165 mm (6.50 in)	Conductor cross-section	1.00 ... 6.00 mm² (AWG 18 ... AWG 10)
		DC link (for braking resistor)	
		Version	Screw-type terminals
		Conductor cross-section	1.00 ... 6.00 mm² (AWG 18 ... AWG 10)
		PE connection	On housing with M5 screw
		Max. motor cable length	
		Shielded	50 m (164.04 ft)
		Unshielded	100 m (328.08 ft)
Standards			
		Compliance with standards	UL, cUL, CE, C-Tick (RCM), SEMI F47
		CE marking	Low-voltage directive 2006/95/EC