



Figure similar

MLFB-Ordering data

6SL3224-0BE34-5AA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.85
Number of phases	3 AC	Offset factor $\cos \varphi$	0.95
Line voltage	380 ... 480 V $\pm 10\%$	Efficiency η	0.97
Line frequency	47 ... 63 Hz	Sound pressure level (1m)	60 dB
Rated current with line reactor	115.00 A	Power loss	1.42 kW
Rated current without line reactor	129.00 A	Ambient conditions	
Output		Cooling	Internal air cooling
Number of phases	3 AC	Cooling air requirement	0.150 m ³ /s (5.297 ft ³ /s)
Rated voltage	400 V	Installation altitude	1000 m (3280.84 ft)
Rated current (LO)	110.00 A	Ambient temperature	
Rated current (HO)	90.00 A	Operation LO	0 ... 40 °C (32 ... 104 °F)
Max. output current	180.00 A	Operation HO	0 ... 50 °C (32 ... 122 °F)
Rated power IEC 400V (LO)	55.00 kW	Transport	-25 ... 55 °C (-13 ... 131 °F)
Rated power NEC 480V (LO)	75.00 hp	Storage	-25 ... 55 °C (-13 ... 131 °F)
Rated power IEC 400V (HO)	45.00 kW	Relative humidity	
Rated power NEC 480V (HO)	60.00 hp	Max. operation	95 % RH, condensation not permitted
Pulse frequency	4 kHz		
Output frequency for vector control	0 ... 200 Hz		
Output frequency for V/f control	0 ... 550 Hz		

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s



Figure similar

MLFB-Ordering data


6SL3224-0BE34-5AA0

Mechanical data

Degree of protection	IP20 / UL open type
Size	FSF
Net weight	52.00 kg (114.64 lb)
Width	350 mm (13.78 in)
Height	934 mm (36.77 in)
Depth	316 mm (12.44 in)

Converter losses to EN 50598-2*

Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	-58.02 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values

Connections

Line side

Version	M8 bolt
Conductor cross-section	25.00 ... 120.00 mm ² (AWG 4 ... AWG -3)

Motor end

Version	M8 bolt
Conductor cross-section	25.00 ... 120.00 mm ² (AWG 4 ... AWG -3)

DC link (for braking resistor)

Version	M8 bolt
Conductor cross-section	25.00 ... 120.00 mm ² (AWG 4 ... AWG -3)

PE connection On housing with M8 screw

Max. motor cable length

Shielded	50 m (164.04 ft)
Unshielded	100 m (328.08 ft)

Standards

Compliance with standards UL, cUL, CE, C-Tick (RCM), SEMI F47

CE marking Low-voltage directive 2006/95/EC